









T512S-01 IBC OIL DISPENSING SYSTEM

WITH HG20R-01 NON-METERED OIL CONTROL GUN (OS900G-01)

10 Year Warranty

*conditions apply

PRODUCT OVERVIEW

The OS900G-01 IBC (Intermediate Bulk Container) mounted oil delivery system incorporates Macnaught's T-Series™ 5:1 pneumatic oil pump, with its low air consumption, high efficiency design, with a ½" x 15m powder coated twin pedestal steel reel specifically selected for its low centre of gravity and low mount roller mouth.

Mounted to a solid galvanised steel base frame, the major components are complimented by quality fixings and intermediate fluid connections. Dispense is via a Macnaught HG20R oil control hose end gun.

The OS900G-01 oil delivery system is shipped complete and ready to be mounted to most standard IBC frames via 4 x J bolts. Fluid connection to the IBC is via the supplied 2" Camlock® fitting and 1" suction hose.

FEATURES & BENEFITS



TECHNICAL SPECIFICATIONS

Pump: T512S-01 5:1 ratio air operated pump

Reel: MOTP1215-01 1/2" x 15m hose reel

Output: SAE10 (8L/min), SAE15W-40 (7L/min), SAE140 (6L/min)

Compatible fluids: oils up to SAE140, ATF's, Engine oil, gear oil,

hydraulic oil, diesel, kerosene, anti-freeze/anti-boil

Min/Max Air Pressure: 400kPa (60psi) / 1,030kPa (150psi)

Minimum air compressor: 0.15m3/min (5cfm)

Air inlet: 1/4" NPT (F)

WETTED COMPONENTS

Aluminium

Zinc

Hard chrome plated steel

Brass

Nitrile

Polyurethane rubber

PACKAGE INCLUDES

Galvanised steel frame

T512S-01 5:1 pump & mounting bracket

MOTP1215-01 hose reel

HG20R-01 non-metered oil control gun

Connecting fittings, hoses, breather and couplers

Instruction manual

For more information visit www.macnaught.com.au/os900g-01

MACNAUGHT Pty Ltd

41-49 Henderson Street Turrella, NSW, 2205 Australia T +61 2 9567 0401

F +61 2 9597 7773

E info@macnaught.com.au

W www.macnaught.com.au

MACNAUGHT USA Inc

614 South Ware Boulevard Tampa, Florida, 33619 United States T +1813 628 5506

F +1509 694 8495

E info@macnaughtusa.com

W www.macnaughtusa.com