

FUEL ACCESSORIES

LH254AS, LH2510N, L-UCFL, L-F0FL, L-PFFL



ANTI-STATIC FUEL HOSE - 1" x 4M WITH 1" BSP FITTINGS

LH254AS

- 1" i.d. anti-static fuel delivery hose suitable for ULP and diesel fuel
- ► 1" BSP (M) crimped fittings
- Suitable for use with Gravity feed, Manual & Electric Fuel Pumps
- ▶ 1" i.d. x 4m hose length
- ► Excellent UV resistance & flexibility
- ▶ 6" strain relieving springs on hose ends
- Max working pressure: 145psi



DIESEL FUEL HOSE - 1" x 10m

LH2510N

- ▶ 1" i.d. Diesel delivery hose Reinforced
- Nitrile rubber hose, diesel and oil
- Suitable for suction and delivery of oils & diesel fuel only
- ► 1" i.d. x 10m hose length
- ► UV stabilised
- ► Operating temperature of -20°C to
- Max working pressure: 300psi



UNIVERSAL CLAMPING FUNNEL

L-UCFL

One size fits all Fits on openings ranging from 1" (25mm) - 3-1/8" (80mm) Suitable for use with light, medium. and high viscosity oils, diesel, detergents and gasoline

FUEL & OIL FUNNEL

L-FOFL

- ► Spout dimensions: 1 3/4" [45mm], 1-1/8" [29mm]
- Suitable for use with diesel urea, and other water based media



PORTABLE FUEL FILTER FUNNEL

L-PFFL

- Anti-static, heavy duty, fast-flow portable funnel
- Filter out free water and solids till 100 microns from fuel
- Suitable for use with diesel. gasoline, kerosene and light oils
- Teflon coated stainless steel filter element





Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205. Australia Ph: 1800 185 102 Fax: +61 2 9597 7773 Email: info@macnaught.com.au Website: macnaught.com