

LUBEMATE POLY DIESEL TANKS

The range of Poly Diesel tanks from Lubemate are the economical alternative for your diesel transport and dispensing requirements. Constructed from durable, high-density rotomolded polyethylene, each tank has an incorporated 12V dispense pump, 4m of hose and an auto-shutoff dispense nozzle. Also included are level gauges and all are protected under a lockable lid.





TANK WARRANTY

PUMP WARRANTY

Backed up with a 3 year warranty on the tanks, and 12 months on the included pumps, these poly tanks and pumps guarantee reliable performance.



TECHNICAL SPECIFICATION

PART NUMBER	DESCRIPTION	FLUID	TANK CAPACITY (L)	FLOW RATES (L/MIN)	VOLTAGE (V)	DUTY CYCLE (MIN)	HOSE LENGTH	DIMENSIONS (W X D X H) MM	WEIGHT (KG)
L-PDT200	LUBEMATE POLY DIESEL TANK 200L	DIESEL	200	40	12 V	30/30	4m x 3/4"	1100 x 800 x 460	35
L-PDT400	LUBEMATE POLY DIESEL TANK 400L	DIESEL	400	40	12 V	30/30	4m x 3/4"	1150 x 800 x 680	53



Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205. Australia Ph: 1800 185 102 Fax: +61 2 9597 7773 Email: info@macnaught.com.au Website: macnaught.com



LUBEMATE POLY DIESEL TANKS - ADBLUE

The range of Poly AdBlue (DEF) and Combo tanks from Lubemate are the economical alternative for transport and dispensing of Diesel Exhaust Fluid and combination Diesel/DEF. Constructed from durable, high-density rotomolded polyethylene, each tank has an incorporated 12V dispense pump, 4m of hose and an auto-shutoff dispense nozzle. Also included are level gauges and all are protected under a lockable lid.





TANK WARRANTY

ARRANTY PUMP WARRANTY

Backed up with a 3 year warranty on the tanks, and 12 months on the included pumps, these poly tanks and pumps guarantee reliable performance.



P/N: L-PCT33050

TECHNICAL SPECIFICATION

PART NUMBER	DESCRIPTION	FLUID	TANK CAPACITY (L)	FLOW RATES (L/MIN)	VOLTAGE (V)	DUTY CYCLE (MIN)	HOSE LENGTH	DIMENSIONS (W X D X H) MM	WEIGHT (KG)
L-PABT200	LUBEMATE POLY ADBLU/ DEF TANK 200L	ADBLUE/DEF	200	26	12 V	30/30	4m x 3/4"	1100 x 800 x 460	35
L-PCT33050	LUBEMATE POLY COMBO DIESEL/ADBLU TANK 330L/50	DIESEL/ ADBLUE	330/50	40/17	12 V	30/30	4m x 3/4"	1150 x 800 x 680	68



Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205. Australia Ph: 1800 185 102 Fax: +61 2 9597 7773 Email: info@macnaught.com.au Website: macnaught.com